

combination wall mounting socket outlet



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 100022 |
| EAN | 4024941192088 |
| Product category | Combined wall mounting socket outlet Quick-Connect twin terminals |
| Current | 16A |
| Number of poles | 5p |
| Number of poles | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 up to 240/415V |
| Frequency | 50 and 60Hz |

| Product description | |
|-----------------------------|--|
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Collar grey RAL 7035 |
| Connection design | with screwless twin terminal |
| Maximum conductor size | 4,0 qmm |
| Cable entry | 1xM25 top, 2xM25 bottom |
| Height | 154mm |
| Width | 83mm |
| Depth | 130mm |
| dimension of enclosure (GG) | 126x83 mm (HxW) |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical information | |
|----------------------------------|---|
| | The cable entry is one at top open and two at bottom closed |
| | 4 cut out fixing holes in the lower part of housing |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.374 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941192088 |
| Length | 130 mm |
| Width | 83 mm |
| Height | 154 mm |
| Weight | 0.375 kg |
| Volume | 1,661.66 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941967921 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 3.966 kg |
| Volume | 17,062.5 ccm |