

panel mounting socket outlet, angled - flange 114x114,
fixing centers 90x90



| Product description | |
|-------------------------------|---|
| BALS-Prd.-Nr | 12001 |
| EAN | 4024941120012 |
| product category (PG) | GT panel mounting socket outlet, angled |
| current (A) | 63A |
| number of poles (P99) | 3p |
| number of poles (P) | 2P+PE |
| position of earth contact (H) | 6 h |
| voltage (V) | 200 up to 250V |

| Product description | |
|--------------------------------|--|
| frequency (HZ) | 50 and 60Hz |
| protection degree (SA) | IP67 |
| colour code 1 (KF1) | blue RAL 5015 |
| Colour of appliance | Hinged lid blue, Bayonet ring grey, Enclosure grey |
| connection design (AT) | screw terminal as box terminal with Kontex-contact |
| maximum conductor size (LQ) | 25.0 qmm |
| cable entry (KE) | null |
| Height | 125mm |
| Width | 114mm |
| Depth | 147mm |
| Flange size vertical | 114mm |
| Flange size horizontal | 114mm |
| Drill hole distance vertical | 90mm |
| Drill hole distance horizontal | 90mm |
| material of enclosure (GM) | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|------------------------|
| | The inclination is 15° |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.475 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941120012 |
| Length | 147 mm |
| Width | 114 mm |
| Height | 125 mm |
| Weight | 0.476 kg |
| Volume | 2,094.75 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941820271 |
| Length | 295 mm |
| Width | 185 mm |
| Height | 215 mm |
| Weight | 2.539 kg |
| Volume | 9,975 ccm |



| Ampere | 63 | 63 | 63 | | | |
|----------------------------|-------|-------|-------|--|--|--|
| Polzahl | 3 | 4 | 5 | | | |
| a | 114,0 | 114,0 | 114,0 | | | |
| b | 114,0 | 114,0 | 114,0 | | | |
| c | 90,0 | 90,0 | 90,0 | | | |
| d | 90,0 | 90,0 | 90,0 | | | |
| e \varnothing | 6,5 | 6,5 | 6,5 | | | |
| f | 12,0 | 12,0 | 12,0 | | | |
| h | 65,0 | 65,0 | 65,0 | | | |
| i | 80,0 | 80,0 | 80,0 | | | |
| k | 92,0 | 92,0 | 92,0 | | | |
| l | 92,0 | 92,0 | 92,0 | | | |
| Leiter mm ² min | 6 | 6 | 6 | | | |
| Leiter mm ² max | 25 | 25 | 25 | | | |