

panel mounting socket outlet, angled - flange 100x92,
fixing centers 85x77



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 120158 |
| EAN | 4024941103831 |
| product group | TE panel mounting socket outlet Quick-Connect, angled |
| current | 32A |
| number of poles | 5p |
| Arrangement of the phases | 3p+N+PE |
| position of earth contact | 7 h |
| voltage (V) | 277/480 up to 288/500V |

| Product description | |
|--------------------------------|--|
| frequency | 50 and 60Hz |
| protection degree | IP67 |
| colour code | black RAL 9005 |
| Colour of appliance | Hinged lid black, Bayonet ring grey, Enclosure grey |
| connection design | screwless sping/cage/kontex |
| maximum conductor size (LQ) | 10,0 qmm |
| cable entry (KE) | null |
| Height | 110mm |
| Width | 101mm |
| Depth | 119mm |
| Flange size vertical | 100mm |
| Flange size horizontal | 92mm |
| Drill hole distance vertical | 85mm |
| Drill hole distance horizontal | 77mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|------------------------|
| | The inclination is 20° |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.27 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941103831 |
| Length | 119 mm |
| Width | 101 mm |
| Height | 110 mm |
| Weight | 0.271 kg |
| Volume | 1,322.09 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941824163 |
| Length | 122 mm |
| Width | 222 mm |
| Height | 538 mm |
| Weight | 3.038 kg |
| Volume | 14,332.32 ccm |



4 MB 115

| Ampere | 16 | 16 | 16 | 32 | 32 | 32 |
|----------------|------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 74,0 | 100,0 | 100,0 | 100,0 | 100,0 | 100,0 |
| b | 62,0 | 92,0 | 92,0 | 92,0 | 92,0 | 92,0 |
| c | 60,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| d | 52,0 | 77,0 | 77,0 | 77,0 | 77,0 | 77,0 |
| e ø | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| f | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 |
| h | 46,0 | 46,0 | 46,0 | 55,0 | 55,0 | 55,0 |
| i | 57,0 | 57,0 | 60,0 | 65,0 | 65,0 | 69,0 |
| k | 57,0 | 65,0 | 70,0 | 75,0 | 75,0 | 78,0 |
| l | 52,0 | 65,0 | 70,0 | 75,0 | 75,0 | 78,0 |
| α | 20° | 20° | 20° | 20° | 20° | 20° |
| Leiter mm² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm² max | 4 | 4 | 4 | 10 | 10 | 10 |