

panel mounting socket outlet, angled - flange 114x114,
fixing centers 90x90




Product description	
BALS-Prd.-Nr	12275
EAN	4024941122757
product category	TE panel mounting socket outlet, angled
current	63A
number of poles	4p
number of poles	3P+PE
position of earth contact	5 h
voltage	600 up to 690V

Product description	
frequency	50 and 60Hz
protection degree	IP44
colour code	black RAL 9005
Colour of appliance	Hinged lid black, Enclosure grey
connection design	screw terminal as box terminal with Kontex-contact
maximum conductor size	25.0 qmm
cable entry	null
Height	119mm
Width	114mm
Depth	148mm
Flange size vertical	114mm
Flange size horizontal	114mm
Drill hole distance vertical	90mm
Drill hole distance horizontal	90mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.46 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941122757
Length	148 mm
Width	114 mm
Height	119 mm
Weight	0.461 kg
Volume	2,007.768 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941837958
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.464 kg
Volume	9,975 ccm



Ampere	63	63	63			
Polzahl	3	4	5			
a	114,0	114,0	114,0			
b	114,0	114,0	114,0			
c	90,0	90,0	90,0			
d	90,0	90,0	90,0			
e ø	6,5	6,5	6,5			
f	12,0	12,0	12,0			
h	65,0	65,0	65,0			
i	81,0	81,0	81,0			
l	92,0	92,0	92,0			
Leiter mm ² min	6	6	6			
Leiter mm ² max	25	25	25			

4 MB 10