

panel mounting socket outlet, angled - flange 85x85,
fixing centers 70x70



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 12867 |
| EAN | 4024941128674 |
| product group | Panel mounting socket outlet Quick-Connect, angled |
| current | 32A |
| number of poles | 3p |
| Arrangement of the phases | 2P+PE |
| position of earth contact | 9 h |
| voltage (V) | 380 up to 415V |

| Product description | |
|--------------------------------|--|
| frequency | 50 and 60Hz |
| protection degree | IP44 |
| colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red, Enclosure grey |
| connection design | screwless sping/cage/kontex |
| maximum conductor size (LQ) | 10,0 qmm |
| cable entry (KE) | null |
| Height | 94mm |
| Width | 85mm |
| Depth | 118mm |
| Flange size vertical | 85mm |
| Flange size horizontal | 85mm |
| Drill hole distance vertical | 70mm |
| Drill hole distance horizontal | 70mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical information | |
|----------------------------------|------------------------|
| | The inclination is 20° |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.185 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941128674 |
| Length | 118 mm |
| Width | 85 mm |
| Height | 94 mm |
| Weight | 0.186 kg |
| Volume | 942.82 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941829458 |
| Length | 128 mm |
| Width | 225 mm |
| Height | 399 mm |
| Weight | 2.109 kg |
| Volume | 11,491.2 ccm |



4 MB 264

| Ampere | 16 | 16 | 16 | 32 | 32 | 32 |
|----------------------------|------|------|------|------|------|------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| b | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| c | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 |
| d | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 |
| e ø | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| f | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 |
| h | 46,0 | 46,0 | 46,0 | 55,0 | 55,0 | 55,0 |
| i | 50,0 | 51,0 | 54,0 | 60,0 | 60,0 | 60,0 |
| l ø | 57,0 | 65,0 | 70,0 | 78,0 | 78,0 | 78,0 |
| α | 20° | 20° | 20° | 20° | 20° | 20° |
| Leiter mm ² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 4 | 4 | 4 | 10 | 10 | 10 |