

panel mounting socket outlet, straight - flange 107x100
fixing centers 85x77




Product description	
BALS-Prd.-Nr	130130
EAN	4024941191289
product group	TE panel mounting socket outlet Quick-Connect, straight
current	63A
number of poles	4p
Arrangement of the phases	3P+PE
position of earth contact	6 h
voltage (V)	380 up to 415V

Product description	
frequency	50 and 60Hz
protection degree	IP44
colour code	red RAL 3000
Colour of appliance	Hinged lid red, Enclosure grey
connection design	screwless spring terminal
maximum conductor size (LQ)	25.0 qmm
cable entry (KE)	null
Height	114mm
Width	110mm
Depth	154mm
Flange size vertical	107mm
Flange size horizontal	100mm
Drill hole distance vertical	85mm
Drill hole distance horizontal	77mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.553 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941191289
Length	154 mm
Width	110 mm
Height	114 mm
Weight	0.554 kg
Volume	1,931.16 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941958585
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.929 kg
Volume	9,975 ccm



	63	63
Ampere	4	5
Polzahl	4	5
a	107,0	107,0
b	100,0	100,0
c	85,0	85,0
d	77,0	77,0
e ø	6,5	6,5
f	12,0	12,0
h	67,0	67,0
i	77,0	77,0
k	110,0	110,0
l ø	88,0	88,0
m	7,0	7,0
Leiter mm ² min	6	6
Leiter mm ² max	25	25

4 MB 265