

panel mounting socket outlet, straight - flange 75x75,
fixing centers 60x60



Product description	
BALS-Prd.-Nr	130158
EAN	4024941190510
product group	Panel mounting socket outlet Quick-Connect twin terminal, straight
current	16A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	6 h
voltage (V)	200/346 up to 240/415V

Product description	
frequency	50 and 60Hz
protection degree	IP67
colour code	red RAL 3000
Colour of appliance	Hinged lid red, Bayonet ring grey, Enclosure grey
connection design	screwless sping/cage/kontex
maximum conductor size (LQ)	4,0 qmm
cable entry (KE)	null
Height	92mm
Width	86mm
Depth	77mm
Flange size vertical	75mm
Flange size horizontal	75mm
Drill hole distance vertical	60mm
Drill hole distance horizontal	60mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, The contacts are brass

Logistics data	
Weight/pcs	0.205 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941190510
Length	77 mm
Width	86 mm
Height	92 mm
Weight	0.206 kg
Volume	609.224 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941830348
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.183 kg
Volume	7,140 ccm

