

flange 75x75, fixing centers 60x60



Product description	
BALS-Prd.-Nr	13182
EAN	4024941131827
product group	TN panel mounting socket outlet Quick-Connect straight
current	16A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	11 h
voltage (V)	250/400 up to 265/460V
frequency	60Hz

Product description	
VG-Type-No.:	VG 96919 AS 003
protection degree	IP67
colour code	bronze-green RAL 6031-F9
Colour of appliance	Bayonet ring bronze-green, Hinged lid bronze-green, Enclosure bronze-green
connection design	screwless sping/cage/kontex
maximum conductor size (LQ)	4,0 qmm
cable entry (KE)	null
Height	92mm
Width	86.5mm
Depth	95mm
Flange size vertical	75mm
Flange size horizontal	75mm
Drill hole distance vertical	60mm
Drill hole distance horizontal	60mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	With bayonet cover on strap

Logistics data	
Weight/pcs	0.22 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941131827
Length	95 mm
Width	86.5 mm
Height	92 mm
Weight	0.221 kg
Volume	756.01 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941838214
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.333 kg
Volume	7,140 ccm



4 MB 125

Ampere Polzahl	16 3	16 4	16 5	32 3	32 4	32 5
a	75,0	75,0	75,0	75,0	75,0	75,0
b	75,0	75,0	75,0	75,0	75,0	75,0
c	60,0	60,0	60,0	60,0	60,0	60,0
d	60,0	60,0	60,0	60,0	60,0	60,0
e ø	5,5	5,5	5,5	5,5	5,5	5,5
f	7,0	7,0	7,0	8,0	8,0	8,0
h	35,0	35,0	35,0	50,0	50,0	50,0
i	57,0	57,0	57,0	69,0	69,0	69,0
k	77,0	83,0	93,0	98,0	98,0	107,0
l ø	45,0	75,0	55,0	60,0	60,0	60,0
m	4,0	7,0	12,0	12,0	12,0	17,0
Leiter mm ² min	1,5	1,5	1,5	2,5	2,5	2,5
Leiter mm ² max	4,0	4,0	4,0	10,0	10,0	10,0