

panel mounting socket outlet, straight - 7 poles, flange 75x75




| Product description | |
|---------------------------|-------------------------------------------|
| BALS-Prd.-Nr | 13326 |
| EAN | 4024941133265 |
| Product category | TE panel mounting socket outlet, straight |
| Current | 16A |
| Number of poles | 7p |
| Number of poles | 6p+PE |
| Position of earth contact | 9 h |
| Voltage | 230V |

| Product description | |
|--------------------------------|----------------------------------------------------------------------------------------------------------|
| Frequency | 50 and 60Hz |
| Protection degree | IP44 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Hinged lid blue RAL 5015, Enclosure grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 4,0 qmm |
| Cable entry | null |
| Height | 86mm |
| Width | 75mm |
| Depth | 71mm |
| Flange size vertical | 75mm |
| Flange size horizontal | 75mm |
| Drill hole distance vertical | 60mm |
| Drill hole distance horizontal | 60mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.192 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941133265 |
| Length | 71 mm |
| Width | 75 mm |
| Height | 86 mm |
| Weight | 0.193 kg |
| Volume | 457.95 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941959025 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 2.045 kg |
| Volume | 5,737.5 ccm |



4 MB 389

| | 16 | 32 | | | | | |
|----------------------------|------|------|--|--|--|--|--|
| Ampere | 16 | 32 | | | | | |
| Polzahl | 7 | 7 | | | | | |
| a | 75,0 | 75,0 | | | | | |
| b | 75,0 | 75,0 | | | | | |
| c | 60,0 | 60,0 | | | | | |
| d | 60,0 | 60,0 | | | | | |
| e ø | 5,5 | 5,5 | | | | | |
| f | 7,0 | 8,0 | | | | | |
| h | 28,0 | 38,0 | | | | | |
| i | 53,0 | 62,0 | | | | | |
| k | 85,0 | 98,0 | | | | | |
| l ø | 60,0 | 60,0 | | | | | |
| m | 11,0 | 17,0 | | | | | |
| Leiter mm ² min | 1,5 | 2,5 | | | | | |
| Leiter mm ² max | 4 | 10 | | | | | |