

# panel mounting socket outlet, straight - 7 poles, flange 75x75





Product description	
BALS-Prd.-Nr	13332
EAN	4024941133326
Product category	GT panel mounting socket outlet straight
Current	32A
Number of poles	7p
Number of poles	6p+PE
Position of earth contact	9 h
Voltage	230V

Product description	
Frequency	50 and 60Hz
Protection degree	IP67
Colour code	blue RAL 5015
Colour of appliance	Hinged lid blue RAL 5015, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	10,0 qmm
Cable entry	null
Height	105mm
Width	101mm
Depth	83mm
Flange size vertical	75mm
Flange size horizontal	75mm
Drill hole distance vertical	60mm
Drill hole distance horizontal	60mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, The contacts are brass

Logistics data	
Weight/pcs	0.316 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941133326
Length	83 mm
Width	101 mm
Height	105 mm
Weight	0.317 kg
Volume	880.215 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941835954
Length	295 mm
Width	185 mm
Height	215 mm
Weight	3.324 kg
Volume	9,975 ccm



Ampere	16	32					
Polzahl	7	7					
a	75,0	75,0					
b	75,0	75,0					
c	60,0	60,0					
d	60,0	60,0					
e ø	5,5	5,5					
f	7,0	8,0					
h	17,0	19,0					
i	57,0	65,0					
k	93,0	106,0					
l ø	55,0	60,0					
m	11,5	17,0					
Leiter mm <sup>2</sup> min	1,5	2,5					
Leiter mm <sup>2</sup> max	4	10					

4 MB 390