

panel mounting socket outlet, straight - flange 120x120,
fixing centers 100x100




Product description	
BALS-Prd.-Nr	13452
EAN	4024941134521
product category	GT panel mounting socket outlet straight
current	125A
number of poles	3p
number of poles	2P+PE
position of earth contact	6 h
voltage	200 up to 250V

Product description	
frequency	50 and 60Hz
protection degree	IP67
colour code	blue RAL 5015
Colour of appliance	Hinged lid blue, Bayonet ring grey, Enclosure grey
connection design	screw terminal as box terminal with Kontex-contact
maximum conductor size	70.0 qmm
cable entry	null
Height	129mm
Width	125mm
Depth	166mm
Flange size vertical	120mm
Flange size horizontal	120mm
Drill hole distance vertical	100mm
Drill hole distance horizontal	100mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.91 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941134521
Length	129 mm
Width	125 mm
Height	129 mm
Weight	0.911 kg
Volume	2,080.125 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941958523
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.776 kg
Volume	17,062.5 ccm



4 MB 55

Ampere Polzahl	125 3	125 4	125 5			
a	120,0	120,0	120,0			
b	120,0	120,0	120,0			
c	100,0	100,0	100,0			
d	100,0	100,0	100,0			
e ø	6,5	6,5	6,5			
f	21,0	21,0	21,0			
h	50,0	50,0	50,0			
i	117,0	117,0	117,0			
k	129,0	129,0	129,0			
l ø	104,0	104,0	104,0			
m	6,0	6,0	6,0			
Leiter mm ² min	25	25	25			
Leiter mm ² max	70	70	70			