

panel mounting socket outlet, straight - flange 75x75,  
fixing centers 60x60



| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 13764  |
| EAN                       | 4024941137645  |
| product group             | Panel mounting socket outlet Quick-Connect, straight |
| current                   | 32A  |
| number of poles           | 5p   |
| Arrangement of the phases | 3p+N+PE  |
| position of earth contact | 10 h   |
| voltage (V)               | > 50V  |

| Product description            |  |
|--------------------------------|--|
| frequency                      | 100 up to 300Hz  |
| protection degree              | IP67   |
| colour code                    | green RAL 6002   |
| Colour of appliance            | Hinged lid green, Bayonet ring grey, Enclosure grey              |
| connection design              | screwless sping/cage/kontex                                      |
| maximum conductor size (LQ)    | 10,0 qmm   |
| cable entry (KE)               | null   |
| Height                         | 105mm  |
| Width                          | 101mm  |
| Depth                          | 110mm  |
| Flange size vertical           | 75mm   |
| Flange size horizontal         | 75mm   |
| Drill hole distance vertical   | 60mm   |
| Drill hole distance horizontal | 60mm   |
| material of enclosure          | Polyamide  |
| contact                        | The contact carrier is made of polyamide, The contacts are brass |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.29 kg / Piece |
| Packaging      | Bag             |
| Content amount | 1 ST            |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941137645 |
| Length         | 110 mm        |
| Width          | 101 mm        |
| Height         | 105 mm        |
| Weight         | 0.291 kg      |
| Volume         | 1,166.55 ccm  |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941830287 |
| Length         | 122 mm        |
| Width          | 222 mm        |
| Height         | 538 mm        |
| Weight         | 3.238 kg      |
| Volume         | 14,332.32 ccm |



| Ampere                     | 16   | 16   | 16   | 32    | 32    | 32    |
|----------------------------|------|------|------|-------|-------|-------|
| Polzahl                    | 3    | 4    | 5    | 3     | 4     | 5     |
| a                          | 75,0 | 75,0 | 75,0 | 75,0  | 75,0  | 75,0  |
| b                          | 75,0 | 75,0 | 75,0 | 75,0  | 75,0  | 75,0  |
| c                          | 60,0 | 60,0 | 60,0 | 60,0  | 60,0  | 60,0  |
| d                          | 60,0 | 60,0 | 60,0 | 60,0  | 60,0  | 60,0  |
| e ø                        | 5,5  | 5,5  | 5,5  | 5,5   | 5,5   | 5,5   |
| f                          | 7,0  | 7,0  | 7,0  | 8,0   | 8,0   | 8,0   |
| h                          | 35,5 | 35,5 | 35,5 | 46,0  | 46,0  | 46,0  |
| i                          | 57,0 | 58,0 | 57,0 | 65,0  | 65,0  | 65,0  |
| k                          | 76,0 | 83,0 | 93,0 | 100,0 | 100,0 | 106,0 |
| l ø                        | 45,0 | 45,0 | 55,0 | 60,0  | 60,0  | 60,0  |
| m                          | 3,5  | 7,0  | 11,5 | 12,0  | 12,0  | 17,0  |
| Leiter mm <sup>2</sup> min | 1,5  | 1,5  | 1,5  | 2,5   | 2,5   | 2,5   |
| Leiter mm <sup>2</sup> max | 4    | 4    | 4    | 10    | 10    | 10    |

4 MB 105