

panel mounting socket outlet, straight - flange 75x75,  
fixing centers 60x60



Product description	
BALS-Prd.-Nr	13773
EAN	4024941137737
Product category	TE panel mounting socket outlet Quick-Connect, straight
Current	32A
Number of poles	3p
Number of poles	2P+PE
Position of earth contact	6 h
Voltage	200 up to 250V

Product description	
Frequency	50 and 60Hz
Protection degree	IP44
Colour code	blue RAL 5015
Colour of appliance	Hinged lid blue RAL 5015, Enclosure grey RAL 7035
Connection design	screwless sping/cage/kontex
Maximum conductor size	10,0 qmm
Cable entry	null
Height	91mm
Width	75mm
Depth	115mm
Flange size vertical	75mm
Flange size horizontal	75mm
Drill hole distance vertical	60mm
Drill hole distance horizontal	60mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.187 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941137737
Length	115 mm
Width	75 mm
Height	91 mm
Weight	0.188 kg
Packaging	Carton
Content amount	10 ST
EAN	4024941831253
Length	258 mm
Width	183 mm
Height	212 mm
Weight	2.022 kg
Volume	8,750 ccm

