

panel mounting socket outlet, straight - flange 70x70x4 fixing centers 56x56



Product description	
BALS-Prd.-Nr	13895
EAN	4024941138956
product group	Panel mounting socket outlet Quick-Connect, straight
current	16A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	6 h
voltage (V)	200/346 up to 240/415V

Product description	
frequency	50 and 60Hz
protection degree	IP44
colour code	red RAL 3000
Colour of appliance	Hinged lid red, Enclosure grey
connection design	screwless sping/cage/kontex
maximum conductor size (LQ)	4,0 qmm
cable entry (KE)	null
Height	86mm
Width	70mm
Depth	93mm
Flange size vertical	70mm
Flange size horizontal	70mm
Drill hole distance vertical	56mm
Drill hole distance horizontal	56mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, The contacts are brass

Logistics data	
Weight/pcs	0.146 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941138956
Length	93 mm
Width	70 mm
Height	86 mm
Weight	0.147 kg
Volume	559.86 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941829090
Length	245 mm
Width	177 mm
Height	185 mm
Weight	1.593 kg
Volume	7,140 ccm

