

panel mounting socket outlet, straight - flange 70x70x4 fixing centers 56x56



Product description	
BALS-Prd.-Nr	13896
EAN	4024941138963
product group	Panel mounting socket outlet Quick-Connect, straight
current	32A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	6 h
voltage (V)	200/346 up to 240/415V

Product description	
frequency	50 and 60Hz
protection degree	IP44
colour code	red RAL 3000
Colour of appliance	Hinged lid red, Enclosure grey
connection design	screwless sping/cage/kontex
maximum conductor size (LQ)	10,0 qmm
cable entry (KE)	null
Height	99mm
Width	74mm
Depth	112mm
Flange size vertical	70mm
Flange size horizontal	70mm
Drill hole distance vertical	56mm
Drill hole distance horizontal	56mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, The contacts are brass

Logistics data	
Weight/pcs	0.205 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941138963
Length	112 mm
Width	74 mm
Height	99 mm
Weight	0.206 kg
Volume	820.512 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941821728
Length	128 mm
Width	225 mm
Height	399 mm
Weight	2.309 kg
Volume	11,491.2 ccm

