

wall mounting socket outlet, fused - housing dimension 170x90, with C-type MCB



| Product description | |
|---------------------------|---------------------------------------|
| BALS-Prd.-Nr | 1504 |
| EAN | 4024941015042 |
| product category | TE wall mounting socket outlet, fused |
| current | 16A |
| number of poles | 3p |
| number of poles | 2P+PE |
| position of earth contact | 6 h |
| voltage | 200 up to 250V |

| Product description | |
|------------------------|--|
| frequency | 50 and 60Hz |
| protection degree | IP44 |
| colour code | blue RAL 5015 |
| Colour of appliance | Operating window smoky topaz, Hinged lid blue, Housing bottom grey, Housing top grey |
| connection design | screwless spring terminals as cage clamp with Kontext-contact |
| maximum conductor size | 4,0 qmm |
| cable entry | top entry M20, bottom entry M25/20 |
| Height | 188mm |
| Width | 90mm |
| Depth | 108mm |
| dimension of enclosure | 170x90 mm (HxW) |
| material of enclosure | Polycarbonate |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|---|
| | The cable entry is one at top open and two at bottom closed |
| | Lower part of housing rotatable by 180° |
| | With 1 pole C-type MCB |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.56 kg / Piece |
| Packaging | Carton |
| Content amount | 1 ST |
| EAN | 4024941015042 |
| Length | 205 mm |
| Width | 102 mm |
| Height | 134 mm |
| Weight | 0.62 kg |
| Volume | 2,118.48 ccm |



14 MB 3

| Ampere Polzahl | 16 3 | 16 4 | 16 5 | | | |
|----------------|--------|--------|--------|--|--|--|
| a | 90,0 | 90,0 | 90,0 | | | |
| b | 170,0 | 170,0 | 170,0 | | | |
| c | 77,0 | 77,0 | 77,0 | | | |
| d | 137,5 | 137,5 | 137,5 | | | |
| e | 118,0 | 114,0 | 121,0 | | | |
| f | 188,5 | 188,5 | 190,0 | | | |
| g | 6,0 | 6,0 | 6,0 | | | |
| h ø | 5,5 | 5,5 | 5,5 | | | |
| i | M20 | M20 | M20 | | | |
| k | M20/25 | M20/25 | M20/25 | | | |
| | | | | | | |
| | | | | | | |