

wall mounting socket outlet, switched, interlocked - housing dimensions 225x118



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 16104 |
| EAN | 4024941161046 |
| product category | TE wall mounting socket outlet, switched, interlocked |
| current | 32A |
| number of poles | 3p |
| number of poles | 2P+PE |
| position of earth contact | 6 h |
| voltage | 200 up to 250V |

| Product description | |
|------------------------|---|
| frequency | 50 and 60Hz |
| protection degree | IP67 |
| colour code | blue RAL 5015 |
| Colour of appliance | Hinged lid blue, Bayonet ring grey, Housing screws grey, Housing bottom grey, Housing top grey, Control knob grey |
| connection design | screwless spring terminals as cage clamp with Kontext-contact |
| maximum conductor size | 10,0 qmm |
| cable entry | top entry M25/M25 bottom entry M25 |
| Height | 260mm |
| Width | 118mm |
| Depth | 144mm |
| dimension of enclosure | 225x118 mm (HxW) |
| material of enclosure | Polycarbonate |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | The cable entry is one at top open, one at top is closed, and two at bottom are closed |
| | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 1.23 kg / Piece |
| Packaging | Carton |
| Content amount | 1 ST |
| EAN | 4024941161046 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.355 kg |
| Volume | 5,737.5 ccm |