

wall mounting socket outlet, switched, interlocked, fused, chemically resistant - housing dimensions 460x180, with C-type circuit breaker



| Product description       |                                                             |
|---------------------------|-------------------------------------------------------------|
| BALS-Prd.-Nr              | 17576                                                       |
| EAN                       | 4024941175760                                               |
| product category          | TE wall mounting socket outlet switched, interlocked, fused |
| current                   | 63A                                                         |
| number of poles           | 5p                                                          |
| number of poles           | 3p+N+PE                                                     |
| position of earth contact | 6 h                                                         |

| Product description    |                                                                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| voltage                | 200/346 up to 240/415V                                                                                                                             |
| frequency              | 50 and 60Hz                                                                                                                                        |
| protection degree      | IP44                                                                                                                                               |
| colour code            | red RAL 3000                                                                                                                                       |
| Colour of appliance    | Housing top lightbeige, Hinged lid red, Housing bottom lightbeige, Operating window lightbeige, Control knob lightbeige, Housing screws lightbeige |
| connection design      | screw terminal as box terminal with Kontex-contact                                                                                                 |
| maximum conductor size | 25.0 qmm                                                                                                                                           |
| cable entry            | top entry M40, bottom entry M40/M32                                                                                                                |
| Height                 | 500mm                                                                                                                                              |
| Width                  | 180mm                                                                                                                                              |
| Depth                  | 191mm                                                                                                                                              |
| dimension of enclosure | 460x180 mm (HxW)                                                                                                                                   |
| material of enclosure  | Polycarbonate - Polyethylene terephthalate light beige                                                                                             |
| contact                | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                                           |

| Additional technical information |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
|                                  | The cable entry is one at top and two at bottom open               |
|                                  | In 0-position lockable for 4 padlocks with bow diameter up to 7 mm |
|                                  | With 3 pole C-type MCB                                             |

| Logistics data |                |
|----------------|----------------|
| Weight/pcs     | 0.0 kg / Piece |
| Packaging      | Carton         |
| Content amount | 1 ST           |
| EAN            | 4024941175760  |
| Length         | 560 mm         |
| Width          | 215 mm         |
| Height         | 260 mm         |
| Weight         | 0.462 kg       |
| Volume         | 26,400 ccm     |



12 MB 21

| Ampere  | 16     | 16     | 32     | 32     | 63     | 63     |
|---------|--------|--------|--------|--------|--------|--------|
| Polzahl | 4      | 5      | 4      | 5      | 4      | 5      |
| a       | 134,0  | 134,0  | 134,0  | 134,0  | 180,0  | 180,0  |
| b       | 365,0  | 365,0  | 365,0  | 365,0  | 460,0  | 460,0  |
| c       | 117,0  | 117,0  | 117,0  | 117,0  | 160,0  | 160,0  |
| d       | 348,0  | 348,0  | 348,0  | 348,0  | 440,0  | 440,0  |
| e       | 135,0  | 141,0  | 146,0  | 152,0  | 184,0  | 184,0  |
| f       | 382,0  | 382,0  | 391,0  | 391,0  | 500,0  | 500,0  |
| g Ø     | 6,5    | 6,5    | 6,5    | 6,5    | 8,3    | 8,3    |
| h       | 8,0    | 8,0    | 8,0    | 8,0    | 6,5    | 6,5    |
| i       | M25/32 | M25/32 | M32/40 | M32/40 | M40    | M40    |
| k       | M25/32 | M25/32 | M32/40 | M32/40 | M32/40 | M32/40 |
| l       | 156,0  | 156,0  | 156,0  | 156,0  | 189,0  | 189,0  |