

plug - with screw terminals one piece housing




Product description	
BALS-Prd.-Nr	21002-TLS
EAN	4024941193153
product category	TLS plug with Multi-Grip cable gland
current	16A
number of poles	3p
number of poles	2P+PE
position of earth contact	9 h
voltage	380 up to 415V
frequency	50 and 60Hz

Product description	
protection degree	IP44
colour code	red RAL 3000
Colour of appliance	Enclosure red, Cable gland grey
connection design	screw terminal
maximum conductor size	2,5 qmm
cable entry	Cable gland
Height	143mm
Width	54mm
Depth	59mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, The contacts are brass

Additional technical information	
	one piece housing, Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 8 up to max. 18 mm

Logistics data	
Weight/pcs	0.116 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941193153
Length	59 mm

Logistics data	
Width	54 mm
Height	143 mm
Weight	0.117 kg
Volume	455.598 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941971355
Length	207 mm
Width	162 mm
Height	142 mm
Weight	1.26 kg
Volume	3,750 ccm



Ampere	16	16	16	32	32	32
Polzahl	3	4	5	3	4	5
a ø	54,0	60,0	66,0	71,0	71,0	80,0
b	94,5	98,0	101,0	115,0	115,0	119,0
c	138,0	142,0	145,0	170,0	170,0	174,0
d	101,5	105,5	108,5	124,0	124,0	128,0
e ø	18,0	18,0	18,0	23,0	23,0	23,0
f	56,6	64,0	71,0	76,0	76,0	85,0
Leiter mm ² min	1	1	1	2,5	2,5	2,5
Leiter mm ² max	2,5	2,5	2,5	6	6	6