


plug - with screw terminals one piece housing




Product description	
BALS-Prd.-Nr	21007-TLS
EAN	4024941199148
product category	TLS plug with Multi-Grip cable gland
current	16A
number of poles	4p
number of poles	3P+PE
position of earth contact	10 h
voltage	> 50V
frequency	100 up to 300Hz

Product description	
protection degree	IP44
colour code	green RAL 6002
Colour of appliance	Enclosure green, Cable gland grey
connection design	screw terminal
maximum conductor size	2,5 qmm
cable entry	Cable gland
Height	143mm
Width	60mm
Depth	68mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, The contacts are brass

Additional technical information	
	one piece housing, Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 8 up to max. 18 mm

Logistics data	
Weight/pcs	0.129 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941199148
Length	68 mm

Logistics data	
Width	60 mm
Height	143 mm
Weight	0.13 kg
Volume	583.44 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941962933
Length	248 mm
Width	158 mm
Height	123 mm
Weight	1.387 kg
Volume	3,960 ccm



Ampere	16	16	16	32	32	32
Polzahl	3	4	5	3	4	5
a ø	54,0	60,0	66,0	71,0	71,0	80,0
b	94,5	98,0	101,0	115,0	115,0	119,0
c	138,0	142,0	145,0	170,0	170,0	174,0
d	101,5	105,5	108,5	124,0	124,0	128,0
e ø	18,0	18,0	18,0	23,0	23,0	23,0
f	56,6	64,0	71,0	76,0	76,0	85,0
Leiter mm ² min	1	1	1	2,5	2,5	2,5
Leiter mm ² max	2,5	2,5	2,5	6	6	6