

with cable gland, with closure cap



| Product description | |
|---------------------------|-----------------------|
| BALS-Prd.-Nr | 210078 |
| EAN | 4024941019422 |
| product group | Quick-Connect TN plug |
| current | 32A |
| number of poles | 4p |
| Arrangement of the phases | 3P+PE |
| position of earth contact | 6 h |
| voltage (V) | 380 up to 415V |
| frequency | 50 and 60Hz |

| Product description | |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| VG-Type-No.: | VG 96919 CP 023 |
| Supplynumber: | 5935-12-366-3251 |
| protection degree | IP67 |
| colour code | bronze-green RAL 6031-F9 |
| Colour of appliance | Cable gland bronze-green, Bayonet ring bronze-green, Housing cover bronze-green, Collar bronze-green, Closure cap bronze-green |
| connection design | screwless spring-clamp |
| maximum conductor size (LQ) | 6,0 qmm |
| cable entry (KE) | Cable gland |
| Height | 199mm |
| Width | 94mm |
| Depth | 97mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| | For cable diameter from 11 up to max. 23,5 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |
| | With closure cap |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.348 kg / Piece |

| Logistics data | |
|----------------|---------------|
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941019422 |
| Length | 97 mm |
| Width | 94 mm |
| Height | 199 mm |
| Weight | 0.349 kg |
| Volume | 1,814.482 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941838962 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 3.686 kg |
| Volume | 13,588.4 ccm |



2 MB 95

| Ampere | 16 | 16 | 16 | 32 | 32 | 32 |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a ø | 70,0 | 78,0 | 86,0 | 94,0 | 94,0 | 101,0 |
| b | 103,5 | 104,0 | 105,5 | 127,0 | 127,0 | 129,5 |
| c | 153,5 | 154,0 | 160,5 | 187,0 | 187,0 | 193,5 |
| d | 111,0 | 111,0 | 119,0 | 136,0 | 136,0 | 138,5 |
| e ø | 18,0 | 18,0 | 21,0 | 23,5 | 23,5 | 27,0 |
| f | 75,5 | 82,5 | 91,0 | 96,5 | 96,5 | 104,5 |
| Leiter mm ² min | 1,0 | 1,0 | 1,0 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 2,5 | 2,5 | 2,5 | 6,0 | 6,0 | 6,0 |
| | | | | | | |
| | | | | | | |
| | | | | | | |