

plug - with screwless terminals, for harsh applications



| Product description | |
|-------------------------------|-----------------------|
| BALS-Prd.-Nr | 21350 |
| EAN | 4024941213509 |
| product category (PG) | Quick-Connect TE plug |
| current (A) | 16A |
| number of poles (P99) | 4p |
| number of poles (P) | 3P+PE |
| position of earth contact (H) | 7 h |
| Voltage | 480 up to 500V |
| frequency (HZ) | 50 and 60Hz |

| Product description | |
|-----------------------------|--|
| protection degree (SA) | IP67 |
| colour code 1 (KF1) | black RAL 9005 |
| Colour of appliance | Collar black, Bayonet ring grey, Cable gland grey, Housing cover black |
| connection design (AT) | screwless spring-clamp |
| maximum conductor size (LQ) | 2,5 qmm |
| cable entry (KE) | Cable gland |
| Height | 149mm |
| Width | 79mm |
| Depth | 79mm |
| material of enclosure (GM) | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|---|
| | For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.175 kg / Piece |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941958080 |

| Logistics data | |
|----------------|-----------|
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 1.883 kg |
| Volume | 7,140 ccm |

