

with cable gland, with closure cap



| Product description | |
|---------------------------|------------------------|
| BALS-Prd.-Nr | 21427 |
| EAN | 4024941214278 |
| Product category | QUICK-CONNECT TN plug |
| Current | 32A |
| Number of poles | 5p |
| Number of poles | 3p+N+PE |
| Position of earth contact | 11 h |
| Voltage | 250/400 up to 265/460V |
| Frequency | 60Hz |

| Product description | |
|------------------------|--|
| VG-Type-No.: | VG 96919 CP 007 |
| Supplynumber: | 5935-12-348-5139 |
| Protection degree | IP67 |
| Colour code | bronze-green RAL 6031-F9 |
| Colour of appliance | Cable gland bronze-green RAL 6031-F9, Bayonet ring bronze-green RAL 6031-F9, Housing cover bronze-green RAL 6031-F9, Collar bronze-green RAL 6031-F9, Closure cap bronze-green RAL 6031-F9 |
| Connection design | screwless spring-clamp |
| Maximum conductor size | 6,0 qmm |
| Cable entry | Cable gland |
| Height | 194mm |
| Width | 101.5mm |
| Depth | 104.5mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | For cable diameter from 13 up to max. 27 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |
| | With closure cap |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.403 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941214278 |
| Length | 104.5 mm |
| Width | 101.5 mm |
| Height | 194 mm |
| Weight | 0.404 kg |
| Volume | 2,057.71 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941839020 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 4.256 kg |
| Volume | 17,062.5 ccm |



2 MB 95

| Ampere Polzahl | 16 3 | 16 4 | 16 5 | 32 3 | 32 4 | 32 5 |
|----------------------------|---------|---------|---------|---------|---------|---------|
| a \varnothing | 70,0 | 78,0 | 86,0 | 94,0 | 94,0 | 101,0 |
| b | 103,5 | 104,0 | 105,5 | 127,0 | 127,0 | 129,5 |
| c | 153,5 | 154,0 | 160,5 | 187,0 | 187,0 | 193,5 |
| d | 111,0 | 111,0 | 119,0 | 136,0 | 136,0 | 138,5 |
| e \varnothing | 18,0 | 18,0 | 21,0 | 23,5 | 23,5 | 27,0 |
| f | 75,5 | 82,5 | 91,0 | 96,5 | 96,5 | 104,5 |
| Leiter mm ² min | 1,0 | 1,0 | 1,0 | 2,5 | 2,5 | 2,5 |
| Leiter mm ² max | 2,5 | 2,5 | 2,5 | 6,0 | 6,0 | 6,0 |
| | | | | | | |
| | | | | | | |
| | | | | | | |