


## plug - with screwless terminals, for harsh applications



Product description	
BALS-Prd.-Nr	21838
EAN	4024941218382
product group	Quick-Connect TE plug
current	32A
number of poles	3p
Arrangement of the phases	2P+PE
position of earth contact	4 h
voltage (V)	100 up to 130V
frequency	50 and 60Hz

Product description	
protection degree	IP44
colour code	yellow RAL 1012
Colour of appliance	Collar yellow, Cable gland grey, Housing cover yellow
connection design	screwless spring-clamp
maximum conductor size (LQ)	6,0 qmm
cable entry (KE)	Cable gland
Height	180mm
Width	66mm
Depth	79mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 11 up to max. 23,5 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.236 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941218382

Logistics data	
Length	79 mm
Width	66 mm
Height	180 mm
Weight	0.237 kg
Volume	938.52 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941831635
Length	258 mm
Width	183 mm
Height	212 mm
Weight	2.512 kg
Volume	8,750 ccm

