

wall mounting appliance inlet - with closure cap



Product description	
BALS-Prd.-Nr	24258
EAN	4024941242585
product group	TE wall mounting appliance inlet Quick-Connect
current	16A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	6 h
voltage (V)	200/346 up to 240/415V
frequency	50 and 60Hz

Product description	
protection degree	IP67
colour code	red RAL 3000
Colour of appliance	Closure cap grey, Collar red, Bayonet ring grey, Housing bottom grey, Housing top grey
connection design	screwless spring-clamp
maximum conductor size (LQ)	2,5 qmm
cable entry (KE)	top entry M20
Height	138mm
Width	87mm
Depth	111mm
dimension of enclosure (GG)	84x84 mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	The cable entry is one at top open and one rear sided closed
	With closure cap

Logistics data	
Weight/pcs	0.321 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941242585
Length	111 mm
Width	87 mm
Height	138 mm
Weight	0.322 kg
Volume	1,332.666 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941832953
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.416 kg
Volume	13,588.4 ccm

