

wall mounting appliance inlet - with closure cap



Product description	
BALS-Prd.-Nr	24419
EAN	4024941244190
product group	TE wall mounting appliance inlet Quick-Connect
current	32A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	6 h
voltage (V)	200/346 up to 240/415V
frequency	50 and 60Hz

Product description	
protection degree	IP67
colour code	red RAL 3000
Colour of appliance	Closure cap grey, Collar red, Bayonet ring grey, Housing bottom grey, Housing top grey
connection design	screwless spring-clamp
maximum conductor size (LQ)	6,0 qmm
cable entry (KE)	top entry M25
Height	148mm
Width	100mm
Depth	125mm
dimension of enclosure (GG)	75x90 mm (HxW)
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	The cable entry is one at top open and one rear sided closed
	With closure cap

Logistics data	
Weight/pcs	0.407 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941244190
Length	123 mm
Width	100 mm
Height	146 mm
Weight	0.408 kg
Volume	1,795.8 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941822978
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.296 kg
Volume	17,062.5 ccm

