

with cable gland, with bayonet cover



| Product description | |
|---------------------------|------------------------|
| BALS-Prd.-Nr | 31027 |
| EAN | 4024941310277 |
| product group | TN connector |
| current | 125A |
| number of poles | 5p |
| Arrangement of the phases | 3p+N+PE |
| position of earth contact | 6 h |
| voltage (V) | 200/346 up to 240/415V |
| frequency | 50 and 60Hz |

| Product description | |
|-----------------------------|---|
| VG-Type-No.: | VG 96919 DS 013 |
| Supplynumber: | 5935-12-322-8597 |
| protection degree | IP67 |
| colour code | bronze-green RAL 6031-F9 |
| Colour of appliance | Pusher black, Cable gland bronze-green, Bayonet ring bronze-green, Housing cover bronze-green, Collar bronze-green, Hinged lid bronze-green |
| connection design | kontex contact |
| maximum conductor size (LQ) | 50.0 qmm |
| cable entry (KE) | Cable gland |
| Height | 295mm |
| Width | 125mm |
| Depth | 128mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | with pilot contact |
| | For cable diameter from 26 up to max. 50 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |
| | With bayonet cover on strap |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 1.355 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941310277 |
| Length | 128 mm |
| Width | 125 mm |
| Height | 295 mm |
| Weight | 1.356 kg |
| Volume | 4,720 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941840026 |
| Length | 345 mm |
| Width | 345 mm |
| Height | 217 mm |
| Weight | 7.11 kg |
| Volume | 24,276 ccm |



| Ampere | 63 | 63 | 63 | 125 | 125 | 125 |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a ø | 110,0 | 110,0 | 110,0 | 125,0 | 125,0 | 125,0 |
| b | 263,0 | 263,0 | 263,0 | 300,0 | 300,0 | 300,0 |
| c | 113,0 | 113,0 | 113,0 | 128,0 | 128,0 | 128,0 |
| d ø | 36,0 | 36,0 | 36,0 | 50,0 | 50,0 | 50,0 |
| Leiter mm ² min | 6,0 | 6,0 | 6,0 | 16,0 | 16,0 | 16,0 |
| Leiter mm ² max | 16,0 | 16,0 | 16,0 | 50,0 | 50,0 | 50,0 |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |