

connector - with screw terminals one piece housing



Product description	
BALS-Prd.-Nr	310345
EAN	4024941097246
product category (PG)	TLS connector Multi-Grip cable gland
current (A)	16A
number of poles (P99)	5p
number of poles (P)	3p+N+PE
position of earth contact (H)	9 h
voltage (V)	120/208 up to 144/250V
frequency (HZ)	50 and 60Hz

Product description	
protection degree (SA)	IP67
colour code 1 (KF1)	blue RAL 5015
Colour of appliance	Enclosure blue, Hinged lid blue, Bayonet ring grey, Cable gland grey
connection design (AT)	screw terminal
maximum conductor size (LQ)	2,5 qmm
cable entry (KE)	Cable gland
Height	160mm
Width	87mm
Depth	92mm
material of enclosure (GM)	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical information	
	one piece housing, Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 8 up to max. 18 mm

Logistics data	
Weight/pcs	0.224 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941097246

Logistics data	
Length	92 mm
Width	87 mm
Height	160 mm
Weight	0.225 kg
Volume	1,280.64 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941835015
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.373 kg
Volume	7,140 ccm

