

## connector - with screw terminals one piece housing



Product description	
BALS-Prd.-Nr	310346
EAN	4024941097253
product category (PG)	TLS connector Multi-Grip cable gland
current (A)	16A
number of poles (P99)	5p
number of poles (P)	3p+N+PE
position of earth contact (H)	6 h
voltage (V)	200/346 up to 240/415V
frequency (HZ)	50 and 60Hz

Product description	
protection degree (SA)	IP67
colour code 1 (KF1)	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure red RAL 3000, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035
connection design (AT)	with screw terminal
maximum conductor size (LQ)	2,5 qmm
cable entry (KE)	Cable gland
Height	160mm
Width	87mm
Depth	92mm
material of enclosure (GM)	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical information	
	one piece housing, Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 8 up to max. 18 mm

Logistics data	
Weight/pcs	0.22 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941097253

Logistics data	
Length	92 mm
Width	87 mm
Height	160 mm
Weight	0.221 kg
Volume	1,280.64 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941825528
Length	258 mm
Width	183 mm
Height	212 mm
Weight	2.352 kg
Volume	8,750 ccm

