

## connector - with screw terminals one piece housing



Product description	
BALS-Prd.-Nr	310352
EAN	4024941097321
product group	TLS connector Multi-Grip cable gland
current	32A
number of poles	3p
Arrangement of the phases	2P+PE
position of earth contact	9 h
voltage (V)	380 up to 415V
frequency	50 and 60Hz

Product description	
protection degree	IP67
colour code	red RAL 3000
Colour of appliance	Hinged lid red, Enclosure red, Bayonet ring grey, Cable gland grey
connection design	screw terminal
maximum conductor size (LQ)	6,0 qmm
cable entry (KE)	Cable gland
Height	190mm
Width	94mm
Depth	97mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical information	
	one piece housing, Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 11 up to max. 23,5 mm

Logistics data	
Weight/pcs	0.302 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941097321

Logistics data	
Length	97 mm
Width	94 mm
Height	190 mm
Weight	0.303 kg
Volume	1,732.42 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941835053
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.226 kg
Volume	13,588.4 ccm

