

## connector - with screwless terminals, for harsh applications



Product description	
BALS-Prd.-Nr	310490
EAN	4024941146937
product group	Quick Connect TE connector
current	63A
number of poles	4p
Arrangement of the phases	3P+PE
position of earth contact	6 h
voltage (V)	380 up to 415V

Product description	
frequency	50 and 60Hz
protection degree	IP44
colour code	red RAL 3000
Colour of appliance	Pusher grey, Housing cover red, Collar red, Hinged lid red, Cable gland grey
connection design	screwless spring terminal
maximum conductor size (LQ)	16,0 qmm
cable entry (KE)	Cable gland
Height	252mm
Width	97mm
Depth	109mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.74 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941146937
Length	109 mm
Width	97 mm
Height	252 mm
Weight	0.741 kg
Volume	2,664.396 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941950091
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.906 kg
Volume	13,588.4 ccm

