

connector - with screwless terminals, for harsh applications



| Product description | |
|---------------------------|----------------------------|
| BALS-Prd.-Nr | 310519 |
| EAN | 4024941145558 |
| product group | Quick Connect TE connector |
| current | 16A |
| number of poles | 4p |
| Arrangement of the phases | 3P+PE |
| position of earth contact | 1 h |
| voltage (V) | >50V for all other |

| Product description | |
|-----------------------------|--|
| protection degree | IP44 |
| colour code | gray RAL 7035 |
| Colour of appliance | Hinged lid grey, Cable gland grey, Enclosure grey |
| connection design | screwless sping/cage/kontex |
| maximum conductor size (LQ) | 2,5 qmm |
| cable entry (KE) | Cable gland |
| Height | 162mm |
| Width | 58mm |
| Depth | 78mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|---|
| | For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.168 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941145558 |

| Logistics data | |
|----------------|---------------|
| Length | 78 mm |
| Width | 58 mm |
| Height | 162 mm |
| Weight | 0.169 kg |
| Volume | 732.888 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941836340 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.805 kg |
| Volume | 5,737.5 ccm |

