

for Event technology



Product description	
BALS-Prd.-Nr	310771
EAN	4024941786850
product group	TE connector
current	63A
number of poles	3p
Arrangement of the phases	2P+PE
position of earth contact	6 h
voltage (V)	200 up to 250V
frequency	50 and 60Hz

Product description	
protection degree	IP67
colour code	blue RAL 5015
Colour of appliance	Collar black, Pusher black, Hinged lid black, Housing cover black, Cable gland black
connection design	kontex contact
maximum conductor size (LQ)	16,0 qmm
cable entry (KE)	Cable gland
Height	251mm
Width	110mm
Depth	115mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.667 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941786850

Logistics data	
Length	115 mm
Width	110 mm
Height	251 mm
Weight	0.668 kg
Volume	3,175.15 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941786867
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.541 kg
Volume	13,588.4 ccm