

with cable gland, with bayonet cover



Product description	
BALS-Prd.-Nr	31150
EAN	4024941311502
Product category	QUICK-CONNECT TN connector
Current	16A
Number of poles	5p
Number of poles	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 up to 240/415V
Frequency	50 and 60Hz

Product description	
VG-Type-No.:	VG 96919 DS 001
Supplynumber:	5935-12-300-3600
Protection degree	IP67
Colour code	bronze-green RAL 6031-F9
Colour of appliance	Cable gland bronze-green RAL 6031-F9, Bayonet ring bronze-green RAL 6031-F9, Hinged lid bronze-green RAL 6031-F9, Enclosure bronze-green RAL 6031-F9
Connection design	screwless sping/cage/kontex
Maximum conductor size	2,5 qmm
Cable entry	Cable gland
Height	168mm
Width	87mm
Depth	92mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 10 up to max. 21 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings
	With bayonet cover on strap

Logistics data	
Weight/pcs	0.239 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941311502
Length	92 mm
Width	87 mm
Height	168 mm
Weight	0.24 kg
Volume	1,344.672 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941839747
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.554 kg
Volume	9,975 ccm



3 MB 70



Ampere	16	16	16	32	32	32
Polzahl	3	4	5	3	4	5
a \varnothing	70,5	78,0	86,5	94,0	94,0	101,5
b	161,0	161,0	168,0	196,0	196,0	200,0
c	77,0	83,0	93,0	99,0	99,0	107,0
d \varnothing	18,0	18,0	21,0	23,0	23,0	27,0
Leiter mm ² min	1,0	1,0	1,0	2,5	2,5	2,5
Leiter mm ² max	2,5	2,5	2,5	6,0	6,0	6,0