

with cable gland, with bayonet cover



Product description	
BALS-Prd.-Nr	31151
EAN	4024941311519
product group	Quick-Connect TN connector
current	32A
number of poles	5p
Arrangement of the phases	3p+N+PE
position of earth contact	6 h
voltage (V)	200/346 up to 240/415V
frequency	50 and 60Hz

Product description	
VG-Type-No.:	VG 96919 DS 005
Supplynumber:	5935-12-300-3597
protection degree	IP67
colour code	bronze-green RAL 6031-F9
Colour of appliance	Cable gland bronze-green, Bayonet ring bronze-green, Hinged lid bronze-green, Enclosure bronze-green
connection design	screwless sping/cage/kontex
maximum conductor size (LQ)	6,0 qmm
cable entry (KE)	Cable gland
Height	200mm
Width	101.5mm
Depth	106mm
material of enclosure	Polyamide
contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 13 up to max. 27 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings
	With bayonet cover on strap

Logistics data	
Weight/pcs	0.407 kg / Piece

Logistics data	
Packaging	Bag
Content amount	1 ST
EAN	4024941311519
Length	106 mm
Width	101.5 mm
Height	200 mm
Weight	0.408 kg
Volume	2,151.8 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941967976
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.296 kg
Volume	17,062.5 ccm

