

connector - with screwless terminals, for harsh applications



| Product description | |
|---------------------------|----------------------------|
| BALS-Prd.-Nr | 31298 |
| EAN | 4024941312981 |
| product group | Quick Connect TE connector |
| current | 16A |
| number of poles | 3p |
| Arrangement of the phases | 2P+PE |
| position of earth contact | 4 h |
| voltage (V) | 100 up to 130V |

| Product description | |
|-----------------------------|--|
| frequency | 50 and 60Hz |
| protection degree | IP67 |
| colour code | yellow RAL 1012 |
| Colour of appliance | Hinged lid yellow, Enclosure yellow, Bayonet ring grey, Cable gland grey |
| connection design | screwless sping/cage/kontex |
| maximum conductor size (LQ) | 2,5 qmm |
| cable entry (KE) | Cable gland |
| Height | 163mm |
| Width | 71mm |
| Depth | 77mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|---|
| | For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.175 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941312981 |
| Length | 77 mm |
| Width | 71 mm |
| Height | 163 mm |
| Weight | 0.176 kg |
| Volume | 891.121 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941968324 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.875 kg |
| Volume | 5,737.5 ccm |

