

with cable gland, with bayonet cover



Product description	
BALS-Prd.-Nr	31323
EAN	4024941313230
Product category	QUICK-CONNECT TN connector
Current	32A
Number of poles	5p
Number of poles	3p+N+PE
Position of earth contact	2 h
Voltage	> 50V
Frequency	over 300 up to 500Hz

Product description	
VG-Type-No.:	VG 96919 DS 008
Supplynumber:	5935-12-312-4196
Protection degree	IP67
Colour code	bronze-green RAL 6031-F9
Colour of appliance	Cable gland bronze-green RAL 6031-F9, Bayonet ring bronze-green RAL 6031-F9, Hinged lid bronze-green RAL 6031-F9, Enclosure bronze-green RAL 6031-F9
Connection design	screwless sping/cage/kontex
Maximum conductor size	6,0 qmm
Cable entry	Cable gland
Height	200mm
Width	101.5mm
Depth	106mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 13 up to max. 27 mm, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings
	With bayonet cover on strap

Logistics data	
Weight/pcs	0.43 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941313230
Length	106 mm
Width	101.5 mm
Height	200 mm
Weight	0.431 kg
Volume	2,151.8 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941839945
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.526 kg
Volume	17,062.5 ccm



3 MB 70



Ampere Polzahl	16 3	16 4	16 5	32 3	32 4	32 5
a Ø	70,5	78,0	86,5	94,0	94,0	101,5
b	161,0	161,0	168,0	196,0	196,0	200,0
c	77,0	83,0	93,0	99,0	99,0	107,0
d Ø	18,0	18,0	21,0	23,0	23,0	27,0
Leiter mm ² min	1,0	1,0	1,0	2,5	2,5	2,5
Leiter mm ² max	2,5	2,5	2,5	6,0	6,0	6,0