

wall mounting socket outlet - housing dimensions 80x70



| Product description | |
|-------------------------------|---------------------------------|
| BALS-Prd.-Nr | 4112 |
| EAN | 4024941041126 |
| product category (PG) | ELV wall mounting socket outlet |
| current (A) | 32A |
| number of poles (P99) | 2p |
| number of poles (P) | 2P |
| position of earth contact (H) | 12 h |
| voltage (V) | 40 up to 50V |
| frequency (HZ) | 50 and 60Hz |

| Product description | |
|-----------------------------|--|
| protection degree (SA) | IP44 |
| colour code 1 (KF1) | gray RAL 7035 |
| Colour of appliance | Hinged lid grey, Housing bottom grey, Housing top grey, Collar grey |
| connection design (AT) | screw terminal |
| maximum conductor size (LQ) | 10,0 qmm |
| cable entry (KE) | top entry M25 |
| Height | 113mm |
| Width | 70mm |
| Depth | 79mm |
| dimension of enclosure (GG) | 80x70 mm (HxW) |
| material of enclosure (GM) | Polyamide |
| contact | The contact carrier is made of polyamide, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|------------------------------------|
| | The cable entry is one at top open |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.177 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941041126 |

| Logistics data | |
|----------------|---------------|
| Length | 79 mm |
| Width | 70 mm |
| Height | 113 mm |
| Weight | 0.178 kg |
| Volume | 624.89 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941969055 |
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 1.903 kg |
| Volume | 7,140 ccm |



16 MB 11

| Ampere | 16 | 16 | 32 | 32 | | |
|----------------------------|-------|-------|-------|-------|--|--|
| Polzahl | 2 | 3 | 2 | 3 | | |
| a | 70,0 | 70,0 | 70,0 | 70,0 | | |
| b | 80,0 | 80,0 | 80,0 | 80,0 | | |
| c | 113,0 | 113,0 | 113,0 | 113,0 | | |
| d | 80,0 | 80,0 | 80,0 | 80,0 | | |
| e | 55,0 | 55,0 | 55,0 | 55,0 | | |
| f | 11,0 | 11,0 | 11,0 | 11,0 | | |
| h ø | 5,2 | 5,2 | 5,2 | 5,2 | | |
| i | 5,0 | 5,0 | 5,0 | 5,0 | | |
| Leiter mm ² min | 4 | 4 | 4 | 4 | | |
| Leiter mm ² max | 10 | 10 | 10 | 10 | | |
| | | | | | | |
| | | | | | | |