

panel mounting socket outlet - straight execution, flange 55x55, fixing centers 45x45




| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 4320 |
| EAN | 4024941043205 |
| product category | ELV panel mounting socket outlet, straight |
| current | 32A |
| number of poles | 3p |
| number of poles | 3P |
| position of earth contact | 2 h |
| voltage | 20 up to 25 and 40 up to 50V |

| Product description | |
|--------------------------------|--|
| frequency | 300Hz |
| protection degree | IP44 |
| colour code | green RAL 6002 |
| Colour of appliance | Hinged lid green, Enclosure grey |
| connection design | screw terminal |
| maximum conductor size | 10,0 qmm |
| cable entry | null |
| Height | 67mm |
| Width | 55mm |
| Depth | 59mm |
| Flange size vertical | 55mm |
| Flange size horizontal | 55mm |
| Drill hole distance vertical | 45mm |
| Drill hole distance horizontal | 45mm |
| material of enclosure | Polyamide |
| contact | The contact carrier is made of polyamide, the contacts are brass nickel plated |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.13 kg / Piece |
| Packaging | Carton |
| Content amount | 10 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941836630 |
| Length | 207 mm |
| Width | 162 mm |
| Height | 142 mm |
| Weight | 1.4 kg |
| Volume | 3,750 ccm |



16 MB 13

| Ampere Polzahl | 16 2 | 16 3 | 32 2 | 32 3 | | |
|----------------------------|---------|---------|---------|---------|--|--|
| a | 55,0 | 55,0 | 55,0 | 55,0 | | |
| b | 55,0 | 55,0 | 55,0 | 55,0 | | |
| c | 45,0 | 45,0 | 45,0 | 45,0 | | |
| d | 45,0 | 45,0 | 45,0 | 45,0 | | |
| e ø | 5,2 | 5,2 | 5,2 | 5,2 | | |
| f | 6,0 | 6,0 | 6,0 | 6,0 | | |
| h | 22,0 | 22,0 | 22,0 | 22,0 | | |
| i | 37,0 | 37,0 | 37,0 | 37,0 | | |
| k | 67,0 | 67,0 | 67,0 | 67,0 | | |
| l ø | 49,0 | 49,0 | 49,0 | 49,0 | | |
| m | 12,0 | 12,0 | 12,0 | 12,0 | | |
| Leiter mm ² min | 4 | 4 | 4 | 4 | | |
| Leiter mm ² max | 10 | 10 | 10 | 10 | | |