

## connector - with cable gland, Multi-Grip




Product description	
BALS-Prd.-Nr	4526
EAN	4024941045261
product group	ELV connector
current	16A
number of poles	2p
Arrangement of the phases	2P
position of earth contact	3 h
voltage (V)	20 up to 25 and 40 up to 50V
frequency	400Hz

Product description	
protection degree	IP44
colour code	green RAL 6002
Colour of appliance	Hinged lid green, Housing cover grey, Cable gland grey, Collar grey
connection design	screw terminal
maximum conductor size (LQ)	10,0 qmm
cable entry (KE)	Cable gland
Height	152mm
Width	62mm
Depth	67mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated


Additional technical information	
	Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 11 up to max. 23,5 mm

Logistics data	
Weight/pcs	0.17 kg / Piece
Packaging	Carton
Content amount	10 ST
EAN	4024941837682

Logistics data	
Length	248 mm
Width	158 mm
Height	123 mm
Weight	1.797 kg
Volume	3,960 ccm



16 MB 44



Ampere Polzahl	16 2	16 3	32 2	32 3			
a	62,0	62,0	62,0	62,0			
b	96,0	96,0	96,0	96,0			
c	152,0	152,0	152,0	152,0			
d	67,0	67,0	67,0	67,0			
e ø	24,5	24,5	24,5	24,5			
Leiter mm <sup>2</sup> min	4	4	4	4			
Leiter mm <sup>2</sup> max	10	10	10	10			

