

connector - with cable gland, Multi-Grip




Product description	
BALS-Prd.-Nr	4528
EAN	4024941045285
product group	ELV connector
current	16A
number of poles	3p
Arrangement of the phases	3P
position of earth contact	no minor keyway
voltage (V)	20 up to 25v
frequency	50 and 60Hz

Product description	
protection degree	IP44
colour code	violet RAL 4005
Colour of appliance	Housing cover grey, Cable gland grey, Hinged lid violet, Collar grey
connection design	screw terminal
maximum conductor size (LQ)	10,0 qmm
cable entry (KE)	Cable gland
Height	125mm
Width	62mm
Depth	67mm
material of enclosure	Polyamide
contact	The contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical information	
	Multi-Grip cable gland with gasket and integrated strain relief, For cable diameter from 11 up to max. 23,5 mm

Logistics data	
Weight/pcs	0.205 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941045285

Logistics data	
Length	67 mm
Width	62 mm
Height	125 mm
Weight	0.206 kg
Volume	519.25 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941819558
Length	275 mm
Width	175 mm
Height	137 mm
Weight	2.175 kg
Volume	5,737.5 ccm



16 MB 44

Ampere Polzahl	16 2	16 3	32 2	32 3
a	62,0	62,0	62,0	62,0
b	96,0	96,0	96,0	96,0
c	152,0	152,0	152,0	152,0
d	67,0	67,0	67,0	67,0
e ø	24,5	24,5	24,5	24,5
Leiter mm ² min	4	4	4	4
Leiter mm ² max	10	10	10	10

